

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

Injeksjonssement 25, Brevik - CEM I 52,5 R



The Norwegian EPD Foundation

Owner of the declaration

Heidelberg Materials Sement Norge AS

Product

Injeksjonssement 25, Brevik - CEM I 52,5 R

Declared unit

1 tonne

This declaration is based on Product Category Rules

EN 15804:2012+A2:2019 serves as core PCR
EN 16908:2017 Cement and building lime

Program operator

The Norwegian EPD Foundation

Declaration number

NEPD-11499-11419

Registration number

NEPD-11499-11419

Issue date

23.06.2025

Valid to

23.06.2030

EPD software:

LCA.no EPD generator ID: 971618

General information

Product

Injeksjonssement 25, Brevik - CEM I 52,5 R

Program operator

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-norge.no

Declaration number

NEPD-11499-11419

This declaration is based on Product Category Rules

EN 15804:2012+A2:2019 serves as core PCR
EN 16908:2017 Cement and building lime

Statement of liability

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit

1 tonne Injeksjonssement 25, Brevik - CEM I 52,5 R

Declared unit with option

A1-A3, A4

Functional unit

General information on verification of EPD from EPD tools

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Verification of EPD tool

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPD Norway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier

Ellen Soldal, Norsus AS

(no signature required)

Owner of the declaration

Heidelberg Materials Sement Norge AS
Contact person: Ingrid Vik Jondahl
e-mail: ingridvik.jondahl@heidelbergmaterials.com

Manufacturer

Heidelberg Materials Sement Norge AS
Lilleakerveien 2A
0283 Oslo, Norway
Contact person: Ingrid Vik Jondahl
e-mail: ingridvik.jondahl@heidelbergmaterials.com
Phone:

Place of production

Pr. Site Heidelberg Materials - Brevik
Setreveien 2
3950 Brevik, Norway

Management system

ISO 14001, ISO 9001

Organisation no

934 949 145

Issue date

23.06.2025

Valid to

23.06.2030

Year of study

2024

Comparability

EPDs of construction products may not be comparable if they do not comply with EN 15804 and are seen in a building context.

Development and verification of EPD

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.

Developer of EPD Ingrid Vik Jondahl

Reviewer of company-specific input data and EPD Petter Thyholdt

Approved



Håkon Hauan, CEO EPD-Norge

Product

Product description

The cement is prepared by fine grinding of Industrisement which satisfies the requirements in NS-EN 197-1: 2011 for CEM I 52,5R. Injeksjonssement 25 also satisfies The Norwegian Public Roads Administration's requirements in Process Code 1-R761 regarding PSD d95 <25 µm.

Product specification

Portland cement

| Materials | Value | Unit |
|--------------------|--------|------|
| Clinker | 95-100 | % |
| Minor constituents | 0-5 | % |
| Gypsum | 0-7 | % |

Technical data

Market

Norway, Europe

Reference service life, product

Reference service life, building or construction works

For cement the reference service life of the building is not relevant.

LCA, Calculation rules

Declared unit

1 tonne Injeksjonssement 25, Brevik - CEM I 52,5 R

Cut-off criteria

All major raw materials and all the essential energy are included. The production processes for raw materials and energy flows with very small amounts (less than 1%) may not be included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation

Allocation is carried out in accordance with the provisions of EN 15804. Incoming energy, water consumption, and in-house waste generation are distributed equally among all products using mass allocation. The standard's guidelines are also applied to co-products. If the allocation factor is 1% or less, economic allocation is deemed negligible and therefore omitted. Additionally, where relevant, the processing and transportation of co-products are included in the analysis.

Data quality

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.


| Materials | Source | Data quality | Year |
|-----------------------------|----------------|--------------|------|
| Additives | ecoinvent 3.10 | Database | 2023 |
| Emissions and waste streams | LCA.no | Database | 2024 |
| Explosives | ecoinvent 3.10 | Database | 2023 |
| Gypsum | ecoinvent 3.10 | Database | 2023 |
| Materials | LCA.no | Database | 2024 |
| Others | LCA.no | Database | 2024 |
| Raw materials, Mineral | Supplier | Project EPD | 2021 |

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

| Product stage | | | Construction installation stage | | Use stage | | | | | | | End of life stage | | | | Beyond the system boundaries |
|---------------|-----------|---------------|---------------------------------|----------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|--------------------------------------|
| Raw materials | Transport | Manufacturing | Transport | Assembly | Use | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery - Recycling-potential |
| A1 | A2 | A3 | A4 | A5 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | C1 | C2 | C3 | C4 | D |
| X | X | X | X | MND | MND | MND | MND | MND | MND | MND | MND | MND | MND | MND | MND | MND |

System boundary

Type of the EPD: cradle to gate (A1 – A3) with option A4. The applied system boundaries cover the production of cement including carbon capture and storage up to the finished product at the factory gate. The product stage includes: - Module A1: Extraction and processing of raw materials - Module A2: Transport of raw materials to the factory gate - Module A3: Clinker and cement production The construction process stage includes: - Module A4: Transport



Additional technical information

No further technical information is relevant.

LCA, Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.














The transport scenario presented in A4 refers to a transport with truck over a distance of 100 km.

Different distances can be deviated from this scenario by a proportional conversion.

| Transport from production place to user (A4) | Capacity utilisation, incl. return (%) | Distance (km) | Fuel/Energy Consumption | Unit | Value (l/t) |
|--|--|---------------|-------------------------|-------|-------------|
| Transport Truck, over 32 tonnes, EURO 6 km HM 2023 | 53,3 % | 100 | 0,023 | l/tkm | 2,30 |

LCA, Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

| Environmental impact | | | | |
|---|----------------------------------|------------------------|-----------|----------|
| | Indicator | Unit | A1-A3 | A4 |
|  | GWP-total | kg CO ₂ -eq | 5,62E+02 | 1,04E+01 |
|  | GWP-fossil | kg CO ₂ -eq | 5,62E+02 | 1,04E+01 |
|  | GWP-biogenic | kg CO ₂ -eq | -1,68E-01 | 5,19E-03 |
|  | GWP-luluc | kg CO ₂ -eq | 3,68E-02 | 3,68E-03 |
|  | ODP | kg CFC11 -eq | 1,95E-06 | 2,00E-07 |
|  | AP | mol H ⁺ -eq | 1,19E+00 | 2,45E-02 |
|  | EP-FreshWater | kg P -eq | 1,39E-02 | 7,29E-04 |
|  | EP-Marine | kg N -eq | 3,31E-01 | 6,42E-03 |
|  | EP-Terrestrial | mol N -eq | 3,83E+00 | 6,94E-02 |
|  | POCP | kg NMVOC -eq | 9,91E-01 | 4,25E-02 |
|  | ADP-minerals&metals ¹ | kg Sb-eq | 1,92E-03 | 2,96E-05 |
|  | ADP-fossil ¹ | MJ | 1,84E+03 | 1,55E+02 |
|  | WDP ¹ | m ³ | 3,14E+02 | 7,81E-01 |







GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.

Remarks to environmental impacts











The core GWP indicators declared do not include the emissions from the combustion of waste fuels (GWP, net). The waste status of the waste-based fuels has been proven. The GWP indicators including the emissions from the combustion of waste fuels (GWP, gross) are reported separately in this EPD under "Additional Environmental Information".

| Additional environmental impact indicators | | | | |
|---|---------------------|-------------------|----------|----------|
| Indicator | | Unit | A1-A3 | A4 |
|  | PM | Disease incidence | 9,48E-06 | 1,00E-06 |
|  | IRP ² | kgBq U235 -eq | 3,27E+00 | 1,89E-01 |
|  | ETP-fw ¹ | CTUe | 1,39E+03 | 3,68E+01 |
|  | HTP-c ¹ | CTUh | 1,66E-07 | 1,00E-07 |
|  | HTP-nc ¹ | CTUh | 7,29E-07 | 1,00E-07 |
|  | SQP ¹ | dimensionless | 1,94E+02 | 1,56E+02 |

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)




"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

| Resource use | | | | |
|---|-----------|----------------|----------|----------|
| | Indicator | Unit | A1-A3 | A4 |
|  | PERE | MJ | 8,79E+02 | 2,47E+00 |
|  | PERM | MJ | 0,00E+00 | 0,00E+00 |
|  | PERT | MJ | 8,79E+02 | 2,47E+00 |
|  | PENRE | MJ | 1,08E+03 | 1,55E+02 |
|  | PENRM | MJ | 0,00E+00 | 0,00E+00 |
|  | PENRT | MJ | 1,08E+03 | 1,55E+02 |
|  | SM | kg | 2,21E-01 | 0,00E+00 |
|  | RSF | MJ | 1,03E+03 | 8,47E-04 |
|  | NRSF | MJ | 1,81E+03 | 0,00E+00 |
|  | FW | m ³ | 6,25E+00 | 2,26E-02 |






PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

| End of life - Waste | | | | |
|---|------|------|----------|----------|
| Indicator | | Unit | A1-A3 | A4 |
|  | HWD | kg | 1,32E+01 | 2,26E-01 |
|  | NHWD | kg | 7,61E+01 | 4,53E+00 |
|  | RWD | kg | 1,31E-03 | 4,67E-05 |

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3}$ = 0,009"

| End of life - Output flow | | | | |
|---|-----|------|----------|----------|
| Indicator | | Unit | A1-A3 | A4 |
|  | CRU | kg | 0,00E+00 | 0,00E+00 |
|  | MFR | kg | 1,85E-02 | 0,00E+00 |
|  | MER | kg | 9,49E-05 | 0,00E+00 |
|  | EEE | MJ | 4,33E-04 | 0,00E+00 |
|  | EET | MJ | 6,55E-03 | 0,00E+00 |

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3}$ = 0,009"

| Biogenic Carbon Content | | |
|---|------|---------------------|
| Indicator | Unit | At the factory gate |
| Biogenic carbon content in product | kg C | 0,00E+00 |
| Biogenic carbon content in accompanying packaging | kg C | 0,00E+00 |

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

Electricity consumption during the manufacturing phase is modelled considering the below specified parameters.

| Electricity mix | Source | Amount | Unit |
|-------------------------------|------------------|--------|---------------------------|
| EL Location based kWh NO 2023 | ecoinvent 3.10.1 | 18,29 | g CO ₂ -eq/kWh |

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Additional Environmental Information

| Additional environmental impact indicators required in NPCR Part A for construction products | | | |
|--|------------------------|----------|----------|
| Indicator | Unit | A1-A3 | A4 |
| GWPIOBC | kg CO ₂ -eq | 5,62E+02 | 1,04E+01 |

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

| Additional GWP indicators in accordance with cPCR and more transparent reporting related to CCS | | |
|---|------------------------|-----------|
| Indicator | Unit | A1-A3 |
| GWP-total, gross | kg CO ₂ -eq | 7,11E+02 |
| GWP-fossil, gross | kg CO ₂ -eq | 7,11E+02 |
| GWP-biogenic, gross | kg CO ₂ -eq | -1,68E-01 |
| GWP-luluc, gross | kg CO ₂ -eq | 3,68E-02 |
| GWP-total, net | kg CO ₂ -eq | 5,62E+02 |
| GWP-fossil, net | kg CO ₂ -eq | 5,62E+02 |
| GWP-biogenic, net | kg CO ₂ -eq | -1,68E-01 |
| GWP-luluc, net | kg CO ₂ -eq | 3,68E-02 |
| CWRS | kg CO ₂ -eq | 0,00E+00 |
| CWNRS | kg CO ₂ -eq | 1,49E+02 |
| CC | kg CO ₂ -eq | 4,54E+02 |
| CCS | kg CO ₂ | 0,00E+00 |

GWP-total, gross = Global Warming Potential total, gross (GWP-fossil, gross + GWP-biogenic, gross + GWP-luluc); GWP-fossil, gross = Global Warming Potential fossil fuels, gross ; GWP-biogenic, gross = Global Warming Potential biogenic, gross ; GWP-luluc = Global Warming Potential land use and land use change; GWP-total, net = Global Warming Potential total, net (GWP-total, gross minus CWRS and CWNRS); CWRS = Emissions from combustion of waste from renewable sources (GWP from secondary fuels' combustion considering CH₄ bio emissions); CWNRS = Emissions from combustion of waste from non-renewable sources (GWP from secondary fuels' combustion CO₂ fossil, CO fossil, N₂O and CH₄ bio fossil); GWP-fossil, net = Global Warming Potential fossil fuels, net (GWP-fossil, gross minus CWNRS); GWP-biogenic, net = Global Warming Potential, CC = Emissions from decarbonization of limestone in clinkering (process emissions, clinker), CCS = Carbon capture and storage

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

NPCR Part A: Construction products and services. Ver. 2.0. April 2021, EPD-Norge.

CEN PCR EN 16908:2017 Cement and building lime

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

General Program Instruction for The Norwegian EPD-Foundation, Version 4, 2024

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no report number: 07.21

Vold et al, (2022) EPD generator for CEN PCR EN 16908:2017 Cement and building lime - Background information for PCR application and LCA data, LCA.no report number: 01.22.

Vold et al, (2024) EPD generator for Heidelberg, Cement, EN 16908 Additional background information, specific for Heidelberg Materials, LCA.no report number: 18.24

| | | |
|--|--|---|
|  Global program operator | Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway | Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-norge.no |
|  | Owner of the declaration Heidelberg Materials Sement Norge AS Lilleakerveien 2A, 0283 Oslo, Norway | Phone: e-mail: ingridvik.jondahl@heidelbergmaterials.com web: www.sement.heidelbergmaterials.no |
|  | Manufacturer Heidelberg Materials Sement Norge AS Lilleakerveien 2A, 0283 Oslo, Norway | Phone: e-mail: ingridvik.jondahl@heidelbergmaterials.com web: www.sement.heidelbergmaterials.no |
|  | Author of the Life Cycle Assessment LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway | Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no |
|  | Developer of EPD generator LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway | Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no |
|  | ECO Platform ECO Portal | web: www.eco-platform.org web: ECO Portal |